

Rittal – The System.

Faster – better – everywhere.

Compact enclosures AE – AE 1050.500

Date : Jan 24, 2020

ENCLOSURES

POWER DISTRIBUTION

CLIMATE CONTROL

IT INFRASTRUCTURE

SOFTWARE & SERVICES

FRIEDHELM LOH GROUP



Compact enclosures AE – AE 1050.500

created: 24.01.2020 build on www.rittal.com/in-en



Product description

Material:	Enclosure: Sheet steel Door: Sheet steel, all-round foamed-in PU seal
Surface finish:	Enclosure and door: Dipcoat primed, powder-coated on the outside, textured paint Mounting plate: Zinc-plated
Colour:	RAL 7035
Protection category IP to IEC 60 529:	IP 66
Protection category NEMA:	NEMA 4
IK Code:	IK08
Supply includes:	Enclosure with hinged door(s), of all-round solid construction Gland plate(s) in enclosure base Mounting plate Lock: 3 mm double-bit
Basic material:	Sheet steel

Product features

Dimensions:	Width: 500 mm Height: 500 mm Depth: 210 mm
Material thickness:	Enclosure: 1.38 mm Door: 1.75 mm Mounting plate: 2.5 mm

Mounting plate:	Width: 449 mm Height: 470 mm
Number of doors:	1
Door hinged on the right, may be swapped to the left:	yes
Lock version:	Cam
Number of locks:	2
Lock insert:	3 mm double-bit
Gland plate, size:	4
Gland plate, qty.:	1
Packs of:	1 pc(s).
Weight/pack:	16.8 kg
EAN:	4028177252073
Customs tariff number:	94032080
ETIM 7.0:	EC000261
ETIM 6.0:	EC000261
eCl@ss 8.0/8.1:	27180101
eCl@ss 6.0/6.1:	27180101
Product description:	AE Compact enclosure, WHD: 500x500x210 mm, Sheet steel, with mounting plate, single-door, with two cam locks

Approvals

Approvals: Bureau Veritas
CSA
DNV-GL
Lloyds Register of Shipping
RRR
Russian Maritime Register of Shipping
TÜV UL + C-UL

Certificates: EAC

IK-Code
Protection category

Declarations:

Declaration of conformity
