

Technical Specifications

Model	H3_210			
Input (DC)				
Max. input voltage	600V			
Operation voltage range	30-550V			
MPP range with Max. power	290-500V			
Start up voltage	>35V			
Rated voltage	380V			
Max. input current	11A			
MPP tracker	1			
Connection type	MC4 1 pair			
DC switch	Yes			
Output (AC)				
Max. output power	3000W / 3000VA			
Max. output current	14.3A			
Rated voltage	220/230V			
AC voltage range	180-280V			
Frequency range	50/60Hz (± 5Hz)			
THD	<3% at Rated Power			
Reactive power	0.8 Ind ~ 0.8 Cap			
Night time power consumption	<2W			
Efficiency				
Peak efficiency	97.5%			
Euro efficiency	97.0%			
Information				
Communication	Wi-Fi			
Indicator	LED			
Display	MyDeltaSolar APP (iOS / Android)			
Cloud	MyDeltaSolar Cloud			
Alarm	Mail Notification			
Certification				
	VDE-AR-N 4105	AS4777.2:2015	EN 61000-6-2	IEC 62109-1/-2
	VDE 0126-1-1/A1	EN50438	EN 61000-6-3	G83/2
General Data				
Operating temp. range	-25°C ~ 60°C			
Protection level	IP65			
Noise emission, typical	20dB (A)			
Operating elevation	<2000m			
Cooling	Natural cooling			
Dimensions (W x H x D) (mm)	380 x 318 x 130			
Weight (kg)	9.2			

- All specifications are subject to change without prior notice.

Inverter Interfaces

H3_210

