



The Power Behind Competitiveness

Delta M10A

Grid-Tied Solar Inverter
M10A



Product Features

- Transformerless Inverter
- Dual MPP Trackers
- Peak Efficiency up to 98.3%
- Wide Voltage Range (200~1000Vdc)
- Reactive Power Control
- Ergonomic Grip Design
- Ultra Compact Size
- Built-in Energy-logger
- IP65 Protection Level
- Built-in AC/DC Switch

www.deltaelectronicsindia.com



DELTA
Smarter. Greener. Together.

Delta M10A

With Delta's cutting-edge technology, the commercial series Solar Inverters are with efficiencies as high as 98.3%. These inverters are compact in size with durable quality to ensure smooth PV system operation. IP65 enclosure provides higher level of protection and enhances its durability in a harsh outdoor environment.



Delta Commercial Series

Technical data M10A

INPUT (DC)	M10A
Maximum Recommended PV power ¹	12.5 kWp
Max. Input Voltage	1000 V
DC Input Voltage Range	200 ~ 1000 V
Start-up Voltage	> 250 V
Start-up Power	40 W
MPPT Voltage Range	200 ~ 1000 V
MPP Voltage Range, Full Power ¹	415 ~ 800 V
Nominal DC Voltage	600 V
Maximum input current; Total (MPPT 1 / MPPT 2)	25 A (15 A / 10 A)
Maximum Short Circuit Current; Total (MPPT 1 / MPPT 2)	39 A (26 A / 13 A)
No. of Independent MPP Trackers	2
Number of DC inputs; Total (MPPT 1 / MPPT 2)	3 (2 / 1)
Maximum Asymmetry	60 / 40 %
Input Connection Type	Multi-Contact MC4
DC Disconnect Switch	Yes (Inbuilt)

OUTPUT (AC)	
Rated Output Power ²	10 kVA
Maximum Output Power ²	10.5 kVA
Rated Output Current	14.5 A
Max. Output Current	16 A
Nominal AC Voltage	3 Ph, 400 V
AC Voltage Range	400 V ± 20 % (320 V ~ 480 V)
Nominal Frequency	50 Hz
Frequency Range	50 Hz ± 10 % (45 Hz ~ 55 Hz)
Power Factor at Rated Power	Unity
Reactive Power (Adjustable)	0.8 Lagging ~ 0.8 Leading
Total Harmonic Distortion	<3% at Rated Power
DC Injection	<0.5% at Rated Output Current
No. of Conductors (user settable)	4/5 Wire (L1, L2, L3, N, PE)
Output Connection Type	Amphenol Connector

EFFICIENCY	
Maximum Efficiency	98.30%
Euro Efficiency	98.00%

PROTECTION	
Input Disconnection Device	Yes
Ground Fault Monitoring / Grid Monitoring	Yes
DC Reverse Polarity Protection	Yes
DC Over Voltage / Current Limitation Protection	Yes
DC / AC Short Circuit Protection	Yes
AC Over Voltage / Current Limitation Protection	Yes
DC / AC Side Surge Protection - Inbuilt	Yes, MOVs

GENERAL DATA	M10A
Dimension (H/W/D)	445 x 510 x 177 mm
Weight	25 kg
Operating Temperature Range	-25°C to +60°C (Power Derating > 46°C)
Relative Humidity	0 ~ 100%, Non-condensing
Maximum Operating Altitude	< 2000 m above sea level
Degree of Protection	IP 65
Noise Level (Typical)	<50 dB (1m Front Panel)
Self Consumption at Night	<2 W
Cooling	Natural Convection

STANDARDS	
Anti-islanding Protection / Grid Regulation	VDE-AR-N 4105; DIN VDE V 0124-100; DIN VDE V 0126-1-1; IEC 61727; IEC 62116
EMC	IEC/EN 61000
Safety	IEC/EN 62109-1 & IEC/EN 62109-2
Efficiency	IEC/EN/DIN 61683
Environmental Testing	IEC 60068-2 (1,2,14,30) & (52)
Ingress Protection	IEC 60529
CE Conformity	Yes

COMMUNICATION ³	
Communication Interface	MODBUS RS 485, Wi-Fi + APP
Digital Inputs	Yes, 6 Nos.
Dry Contacts	Yes, 1 Nos.
Emergency Power Off (EPO)	Yes, 1 Nos.
Display	20 x 4 Digital LCD
Built-in Energy Data Logger	Yes

WARRANTY	
Standard Warranty ³	5 Years

Notes

1. When Operated with Symmetrical DC Inputs (50/50 %)
2. For $\cos \phi = 1$ ($VA = W$)
3. Refer to Delta's Standard Warranty Terms and Conditions for more details.
4. If PV Module is grounded (Negative / Positive Grounding), separate Isolation Transformer is required at the output side of each Inverter.
5. External String Fuses & DC/AC SPDs are recommended.

For Any Sales / Application Engineering Support, Please Contact :

DELTA ELECTRONICS INDIA PVT. LTD.

"A" Block, Third Floor, Ozone Manay Tech Park, Hongasandra Village, Hosur Road, Bangalore – 560 068, INDIA

TEL +91 80 6716 4646

Fax +91 80 6716 4784

www.deltaelectronicsindia.com | email: solarsales@deltaww.com